

VENTFREE Fireboxes



36STFG See-Thru Vent Free Firebox shown with optional pewter louvers and DST Gas Logs.

Imagine having the ability to connect two separate rooms with a single fireplace or divide a room into two living areas, creating a unique, stylish appearance.

High Efficiency, Flexible Solution To *All Your Designer Hearth Needs*

36STFG See-Thru, 36PFG Peninsula and 36(R)(L)CFG Corner Vent Free Fireboxes

36STFG See-Thru Features:

- Full size 36" hearth opening and 24" depth
- Two fireplaces in one
- Standard black louvers for circulating installation
- Radiant face plates included to convert a circulating fireplace into a radiant fireplace in seconds
- Tavern brown firebrick is standard
- Includes black hood, junction box and thermal sensor for blower accessory
- Smartline field-installed accessories include brass louvers, pewter louvers, brass hood and a variable speed blower
- Limited lifetime warranty
- CSA design certified





36PFG Peninsula Vent Free Firebox shown with optional DST Gas Logs.

What a beautiful way to enjoy a roaring fire! The Peninsula offers a three-sided view and unique design possibilities.

When Your Home *Demands A Dramatic Fire*

Designer Series

36PFG Peninsula Features:

- Full size 36" hearth opening and 24" depth
- Contemporary peninsula design offers a three-sided viewing area for a dramatic way to divide or accent any room
- Standard glass end panel
- Standard black louvers for circulating installations
- Radiant face plates included to convert a circulating fireplace to a radiant fireplace in seconds
- Includes black hood, junction box and thermal sensor for blower accessory
- Smartline field-installed accessories include brass louvers, pewter louvers, brass hood and a variable speed blower

- Tavern brown firebrick is standard
- Limited lifetime warranty
- CSA design certified

DST30 Features:

- Multi-sided designer yellow flame log set for use with See-Thru, Peninsula and Corner fireboxes
- 38,000 Btu dual burner system
- 30" artistically crafted multi-log design
- Millivolt control valve with on/off switch and variable flame height control
- Matchless piezo ignition and safety pilot system
- Limited lifetime warranty
- CSA design certified and factory tested

VENTFREE Fireboxes



The Martin Hearth & Heating corner fireplace provides a contemporary, stylish focal point to any room design.

36RCFG Corner Vent Free Firebox shown with optional brass louvers and DST Gas Logs.

The Beauty Of Fire.
The Convenience Of Gas.

Designer Series



DST Vent Free Gas Logs - Side A



DST Vent Free Gas Logs - Side B

36(R)(L)CFG Corner Features:

- Full size 36" hearth opening and 24" depth with standard wire mesh screens
- Right and left corners offer maximum versatility
- Stylish modern appearance enhances the look of any room; providing several options for adding a fireplace to a room with limited wall space
- Standard black louvers for circulating installations
- Tavern brown firebrick is standard
- Includes black hood, junction box and thermal sensor for blower accessory
- Smartline field-installed accessories include brass louvers, pewter louvers, brass hood and a variable speed blower
- Limited lifetime warranty
- CSA design certified

OPTIONS AND SPECIFICATIONS

Product Specifications

Model	Width		Height		Depth		Minimum Hearth Area			Hearth Openin	Radiant or Circulating	Design Certified
	Actual	Framing	Actual	Framing	Actual	Framing	A	B	C			
36STFG	39-1/2"	40"	37-3/4"	38"	23-3/4"	22-1/2"	36"	20-1/4"	21-1/2"	774	Both	CSA
36PFG	39-1/2"	39"	37-3/4"	38"	23-3/4"	22-1/2"	36"	20-1/4"	21-1/2"	774	Both	CSA
36(R/L)CFG	39-1/2"	39"	37-3/4"	38"	23-3/4"	23-1/8"	36"	20-1/4"	21-1/2"	774	Circulating	CSA

OPTIONAL ACCESSORIES



Brass Louvers



Pewter Louvers



Brass Hood



Variable Thermostat Controlled Forced Air Blower

GAS LOGS ACCESSORIES

- Decorative Fiber Ceramic Embers
- Fiber Ceramic Cinders
- Extra Volcanic Rock
- Stainless Steel Flexible Gas Connector
- Damper Clamps

For Remote Operation:



On/Off Hand Held Remote Control with Receiver.



Hand Held Remote Control with 90 min. countdown timer with Receiver.



On/Off Thermostat Remote Control with Receiver.



Hand Held Programmable Thermostat Remote Control with Receiver.



On/Off Thermostat Remote Control with 3-speed blower control with Receiver.



7-Day Programmable On/Off Wireless Wall Thermostat, Battery or 110 Receiver.



Touch Light™ Table Top/Wall Mount TLM On/Off and TL Thermostat Remote Control with Receiver.

REGULATORY APPROVAL

The DST series of vent free gas logs have been tested and approved by CSA as an unvented room heater to the latest ANSI Z21.11 and I.A.S. US5-95 requirements. These units also comply with ANSI Z21.60-1991 "Decorative Gas Appliances" for solid-fuel burning fireplaces. These gas logs are intended for installation into solid-fuel burning fireplaces, or CSA approved unvented fireplaces and are also approved for installation in an aftermarket manufactured (mobile) home, where not prohibited by state or local codes.

The Designer Series fireboxes have been tested and approved to the Z21-91 standard for ventless firebox enclosures.



A Division of MHS, Inc.
149 Cleveland Drive • Paris, KY 40361
www.martinhearthandheating.com

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice.



MADE IN U.S.A.




Hearth, Patio & Barbecue Association



Vent-Free Gas Heat

Minimum Hearth Area Drawing



Note: Please see Product Specification Chart above.

Gas Log Minimum Hearth Area (refer to drawing)

	A	B	C
DST Gas Logs	36"	20-1/4"	21-1/2"

Optional Gas Log Product Specifications

Model	Log Size	Fuel Type	Millivolt Control	Approx. Heating Area (Sq. Ft.)	Approx. Cost to Operate* Per Hour (Low-High)
DST30NV	30"	NG	24,000-38,000	1,300	24¢-38¢
DST30PV	30"	LP	31,000-38,000	1,300	31¢-38¢

* Based on 2003 Dept. of Energy National Average Energy Cost for lowest and highest Btu operation.

Vent Free Fireplace Framing Dimensions

	36STFG	36PFG	36(R/L)CFG
A	19"	19"	21"
B	22-1/2"	22-1/2"	-
B ²	-	-	23-1/8"
C	40"	-	-
C ²	-	39"	39"
D	38"	38"	38"

Please refer to the installation manual for more detailed framing instructions.

Warning:

- It is recommended that the screen be used during operation of this log set. Always ensure the screen has adequate spaces to allow for passage of combustion air to the gas log set.
- Correct installation of the ceramic fiber logs, proper location of the heater and periodic cleaning are necessary to avoid potential service problems with sooting.
- Keep small children and animals away from the open flame of the gas log set at all times.
- There may be a start-up odor associated with the heating of the logs. The odor should diminish in 2-3 hours of operation with the burner at its highest setting with the fan in the off position.

SOLD BY: